


BASES AEREAS / MOBILE SOCKETS**Referencias / References**

3P = 2P + T
4P = 3P + T
5P = 3P + T + N

			110V 50/60Hz	230V 50/60Hz	400V 50/60Hz	500V 50/60Hz
Amp	Poles	Pack unit	Poles: 3P 4P 5P Hour P: 4h 4h 4h	Poles: 3P 4P 6P Hour P: 6h 9h 9h	Poles: 3P 4P 6P Hour P: 9h 6h 6h	Poles: 3P 4P 6P Hour P: 7h 7h 7h
16	3	10	23100	23200	23304	23404
	4	10	23101	23201	23300	23400
	5	5	23104	23202	23301	23401

Ref. / Item **23200****Dimensiones y conexiones / Dimensions & connections**

Poles	16A		
	3	4	5
A	157	157	150
B	85	91	97
C	110	110	110
Ø K	6-15	6-15	8-16
Connection type	Conexión por tornillo / Screw terminals		
Wire flexible (mm²)	1 - 2,5		
Weight (g)	215	230	252

Dimensiones en mm / Dimensions in mm

Características Técnicas / Technical Data

Tensión de utilización / Operating Voltage	■ 100...130V ■ 200...250V ■ 380...415V ■ 480...500V	Normativa aplicada / Applied Regulations	IEC 60309-1, IEC 60309-2 Low Voltage Directive 2014/35/UE
Intensidad nominal / Rated current	16A	Diámetro exterior del cable / External cable diameter	Min: 8,1mm Max: 15,3mm
Frecuencia / Frequency	50/60 Hz	Material / Material	PA6
Resistencia de aislamiento / Insulating Resistance	>10 MΩ	Material de contacto / Contact material	Latón Brass
Rigidez dieléctrica / Dielectric Strength	2,5 kV	Temperatura de funcionamiento / Operating Temperature	-25°C / +40°C
Grado de Protección / Protection degree	IP44-54 (IEC / EN 60529)	Resistencia al impacto / Impact Resistance	IK08 (IEC / EN 62262)
Prueba hilo incandescente / Glow wire test	850°C partes soportan partes activas / parts support live parts 650°C Otras partes / Other parts (IEC / EN 60695-2-10)	Ensayo de bola / Ball pressure test	125°C partes soportan partes activas / parts support live parts 80°C Otras partes / Other parts (IEC / EN 60695-10-2)

Certificaciones / Certifications

Normativa aplicada / Applied Standards	IEC/CEI/EN 60309-1, IEC/CEI/EN 60309-2
Productos certificados / Certified products	VDE: 23100, 23101, 23104, 23200, 23201, 23202, 23304, 23300, 23301, 23404, 23400, 23401